

DATASHEET

NI 9375

16 DI/16 DO, 30 VDC, 7 μ s Sinking DI, 500 μ s Sourcing DO



- DSUB or spring-terminal connectivity
- 60 VDC, DI-bank-to-DO-bank isolation
- 60 VDC, CAT I, channel-to-earth isolation

The NI 9375 is a combination digital input, digital output module for CompactDAQ and CompactRIO systems. The digital input lines are compatible with 24 V logic levels and the digital output lines are compatible with 6 V to 30 V signals, based on the external power supply. The NI 9375 offers 1,000 Vrms withstand isolation from channel to earth ground. It works with industrial logic levels and signals for direct connection to a wide array of industrial switches, transducers, and other devices.

| | |
|--|--|
|  | Kit Contents <ul style="list-style-type: none">• NI 9375• NI 9375 Getting Started Guide• Flathead Screwdriver (Spring Terminal) |
|  | Accessories <ul style="list-style-type: none">• NI 9940 Backshell Connector Kit (Spring Terminal)• NI 9923 Screw-Terminal Block (DSUB) |

| C SERIES DIGITAL MODULE COMPARISON | | | | | |
|------------------------------------|---------------|------------|--------------------------------|----------------------------------|---------------------------------------|
| Product Name | Signal Levels | Channels | Direction | Update Rate | Connectivity |
| NI 9375 | 12 V, 24 V | 8 DI, 8 DO | Sinking Input, Sourcing Output | 7 μ s (DI), 500 μ s (DO) | Spring-Terminal, DSUB |
| NI 9421 | 12 V to 24 V | 8 DI | Sinking Input | 100 μ s | Screw-Terminal, Spring-Terminal, DSUB |
| NI 9425 | 12 V, 24 V | 32 DI | Sinking Input | 7 μ s | DSUB |
| NI 9472 | 6 V to 30 V | 8 DO | Sourcing Output | 100 μ s | Screw-Terminal, Spring-Terminal |
| NI 9476 | 6 V to 30 V | 32 DO | Sourcing Output | 500 μ s | DSUB |

NI C Series Overview



NI provides more than 100 C Series modules for measurement, control, and communication applications. C Series modules can connect to any sensor or bus and allow for high-accuracy measurements that meet the demands of advanced data acquisition and control applications.

- Measurement-specific signal conditioning that connects to an array of sensors and signals
- Isolation options such as bank-to-bank, channel-to-channel, and channel-to-earth ground
- -40 °C to 70 °C temperature range to meet a variety of application and environmental needs
- Hot-swappable

The majority of C Series modules are supported in both CompactRIO and CompactDAQ platforms and you can move modules from one platform to the other with no modification.

CompactRIO



CompactRIO combines an open-embedded architecture with small size, extreme ruggedness, and C Series modules in a platform powered by the NI LabVIEW reconfigurable I/O (RIO) architecture. Each system contains an FPGA for custom timing, triggering, and processing with a wide array of available modular I/O to meet any embedded application requirement.

CompactDAQ

CompactDAQ is a portable, rugged data acquisition platform that integrates connectivity, data acquisition, and signal conditioning into modular I/O for directly interfacing to any sensor or signal. Using CompactDAQ with LabVIEW, you can easily customize how you acquire, analyze, visualize, and manage your measurement data.




Software

LabVIEW Professional Development System for Windows




- Use advanced software tools for large project development
- Generate code automatically using DAQ Assistant and Instrument I/O Assistant
- Use advanced measurement analysis and digital signal processing
- Take advantage of open connectivity with DLLs, ActiveX, and .NET objects
- Build DLLs, executables, and MSI installers

NI LabVIEW FPGA Module




- Design FPGA applications for NI RIO hardware
- Program with the same graphical environment used for desktop and real-time applications
- Execute control algorithms with loop rates up to 300 MHz
- Implement custom timing and triggering logic, digital protocols, and DSP algorithms
- Incorporate existing HDL code and third-party IP including Xilinx IP generator functions
- Purchase as part of the LabVIEW Embedded Control and Monitoring Suite

NI LabVIEW Real-Time Module



- Design deterministic real-time applications with LabVIEW graphical programming
- Download to dedicated NI or third-party hardware for reliable execution and a wide selection of I/O
- Take advantage of built-in PID control, signal processing, and analysis functions
- Automatically take advantage of multicore CPUs or set processor affinity manually
- Take advantage of real-time OS, development and debugging support, and board support
- Purchase individually or as part of a LabVIEW suite

NI 9375 Circuitry



- The bank of 16 digital input channels and the bank of 16 digital output channels on the NI 9375 are isolated from each other and isolated from earth ground.
- The NI 9375 internally limits current signals connected to DI.
- The NI 9375 has sinking inputs. Sinking inputs provide a path to COM when the sourcing device connected to the NI 9375 drives current or applies voltage to DI.
- The NI 9375 has sourcing outputs. Sourcing outputs drive current from V_{sup} to DO when the channel is on.



Tip For more information about sinking inputs and sourcing outputs, visit ni.com/info and enter the Info Code `sinksources`.

Allowable Current Per Module

The NI 9375 has a per module continuous output current specification. Use the following equation to determine whether the total module current of your loads for channels that are turned on are within the specification.

Figure 1. Total Module Current Equation

$$(I_{D00})^2 + (I_{D01})^2 + \dots + (I_{D015})^2 = \text{Total Module Current}$$

For example, an NI 9375 with spring terminal with two channels at 250 mA, six channels at 125 mA, and eight channels at 62 mA has the following per module continuous output current.

Figure 2. Total Module Current Example

$$\left\{ \left[(250 \text{ mA})^2 * 2 \right] + \left[(125 \text{ mA})^2 * 6 \right] + \left[(62 \text{ mA})^2 * 8 \right] \right\} = 0.25 \text{ A}^2$$

NI 9375 Specifications

The following specifications are typical for the range -40 °C to 70 °C unless otherwise noted. All voltages are relative to COM unless otherwise noted.



Caution Do not operate the NI 9375 in a manner not specified in this document. Product misuse can result in a hazard. You can compromise the safety protection built into the product if the product is damaged in any way. If the product is damaged, return it to NI for repair.

Input/Output Characteristics

| | |
|--------------------|---|
| Number of channels | 32 channels: 16 digital input and 16 digital output |
|--------------------|---|

Digital Input

| | |
|---------------------|-----------------|
| Input type | Sinking |
| Input voltage range | 0 VDC to 30 VDC |

Digital logic levels

OFF state

| | |
|---------------|---------|
| Input voltage | ≤5 V |
| Input current | ≤150 μA |

| | |
|-----------------------------------|-------------------------|
| ON state | |
| Input voltage | ≥ 10 V |
| Input current | ≥ 330 μ A |
| Hysteresis | |
| Input voltage | 1.7 V minimum |
| Input current | 50 μ A minimum |
| Input impedance | 30 k Ω $\pm 5\%$ |
| Setup time ¹ | 1 μ s maximum |
| Update/transfer time ² | 7 μ s maximum |

Digital Output

| | |
|---|----------------------------------|
| Output type | Sourcing |
| Power-on output state | Channels off |
| External power supply voltage range (V _{sup}) | 6 VDC to 30 VDC |
| Continuous output current (I_O) | |
| NI 9375 with spring terminal | |
| All channels on | 125 mA maximum (per channel) |
| One channel on | 500 mA maximum |
| Per module | 0.25 A ² |
| NI 9375 with DSUB | |
| All channels on | 100 mA maximum (per channel) |
| One channel on | 400 mA maximum |
| Per module | 0.16 A ² maximum |
| Output impedance (R_O) | 0.3 Ω maximum |
| Output voltage (V_O) | V _{sup} - ($I_O R_O$) |
| Reversed-voltage protection | None |
| Current limiting | None |
| V _{sup} current consumption | 18 mA |

¹ Setup time is the amount of time input signals must be stable before reading from the module.

² Update/transfer time is the maximum time the software takes to read data from the module. The update/transfer is valid when the module is used in a CompactRIO system. When used in other systems, driver software and system latencies impact this time.

| | |
|-----------------------------------|---------------------|
| Update/transfer time ³ | 7 μ s maximum |
| Propagation delay ⁴ | 500 μ s maximum |

Related Information

[Allowable Current Per Module](#) on page 5

Power Requirements

Power consumption from chassis

| | |
|-------------|--------------------|
| Active mode | 450 mW maximum |
| Sleep mode | 25 μ W maximum |

Thermal dissipation (at 70 °C)

| | |
|-------------|---------------|
| Active mode | 1.5 W maximum |
| Sleep mode | 0.6 W maximum |

Physical Characteristics

If you need to clean the module, wipe it with a dry towel.



Tip For two-dimensional drawings and three-dimensional models of the C Series module and connectors, visit ni.com/dimensions and search by module number.

Spring-terminal wiring

| | |
|---------------------------|--|
| Gauge | 0.08 mm ² to 1.0 mm ² (28 AWG to 18 AWG) copper conductor wire |
| Wire strip length | 7 mm (0.28 in.) of insulation stripped from the end |
| Temperature rating | 90 °C minimum |
| Wires per spring terminal | One wire per spring terminal |

Connector securement

| | |
|--------------------------|---------------------------|
| Securement type | Screw flanges provided |
| Torque for screw flanges | 0.2 N · m (1.80 lb · in.) |

Weight

| | |
|------------------------------|----------------|
| NI 9375 with spring terminal | 159 g (5.6 oz) |
| NI 9375 with DSUB | 148 g (5.3 oz) |

³ *Update/transfer time* is the maximum time the software takes to write data to the module. The update/transfer is valid when the module is used in a CompactRIO system. When used in other systems, driver software and system latencies impact this time.

⁴ *Propagation delay* is the amount of time it takes the output signals to change state after being written to.

Safety Voltages

Connect only voltages that are within the following limits:

| | |
|-------------------------------|---|
| Channel-to-COM or Vsup-to-COM | 30 VDC maximum |
| Isolation | |
| DI bank-to-DO bank | 60 VDC maximum |
| Channel-to-Channel | No isolation between channels |
| Channel-to-earth ground | |
| Continuous | 60 VDC, Measurement Category I |
| Withstand | 1,000 Vrms, verified by a 5 s dielectric withstand test |

Measurement Category I is for measurements performed on circuits not directly connected to the electrical distribution system referred to as *MAINS* voltage. MAINS is a hazardous live electrical supply system that powers equipment. This category is for measurements of voltages from specially protected secondary circuits. Such voltage measurements include signal levels, special equipment, limited-energy parts of equipment, circuits powered by regulated low-voltage sources, and electronics.



Caution Do not connect the NI 9375 to signals or use for measurements within Measurement Categories II, III, or IV.



Note Measurement Categories CAT I and CAT O are equivalent. These test and measurement circuits are not intended for direct connection to the MAINS building installations of Measurement Categories CAT II, CAT III, or CAT IV.

Hazardous Locations

| | |
|---|---|
| U.S. (UL) | Class I, Division 2, Groups A, B, C, D, T4; Class I, Zone 2, AEx nA IIC T4 |
| Canada (C-UL) | Class I, Division 2, Groups A, B, C, D, T4; Class I, Zone 2, Ex nA IIC T4 |
| Europe (ATEX) and International (IECEX) | Ex nA IIC T4 Gc |

Safety and Hazardous Locations Standards

This product is designed to meet the requirements of the following electrical equipment safety standards for measurement, control, and laboratory use:

- IEC 61010-1, EN 61010-1
- UL 61010-1, CSA 61010-1
- EN 60079-0:2012, EN 60079-15:2010
- IEC 60079-0: Ed 6, IEC 60079-15; Ed 4

- UL 60079-0; Ed 5, UL 60079-15; Ed 3
- CSA 60079-0:2011, CSA 60079-15:2012



Note For UL and other safety certifications, refer to the product label or the [Online Product Certification](#) section.

Electromagnetic Compatibility

This product meets the requirements of the following EMC standards for electrical equipment for measurement, control, and laboratory use:

- EN 61326-1 (IEC 61326-1): Class A emissions; Industrial immunity
- EN 55011 (CISPR 11): Group 1, Class A emissions
- AS/NZS CISPR 11: Group 1, Class A emissions
- FCC 47 CFR Part 15B: Class A emissions
- ICES-001: Class A emissions



Note For EMC declarations and certifications, refer to the [Online Product Certification](#) section.

CE Compliance

This product meets the essential requirements of applicable European Directives, as follows:

- 2014/35/EU; Low-Voltage Directive (safety)
- 2014/30/EU; Electromagnetic Compatibility Directive (EMC)
- 94/9/EC; Potentially Explosive Atmospheres (ATEX)

Online Product Certification

Refer to the product Declaration of Conformity (DoC) for additional regulatory compliance information. To obtain product certifications and the DoC for this product, visit ni.com/certification, search by model number or product line, and click the appropriate link in the Certification column.

Shock and Vibration

To meet these specifications, you must panel mount the system.

Operating vibration

| | |
|----------------------------------|--|
| Random (IEC 60068-2-64) | 5 g _{rms} , 10 Hz to 500 Hz |
| Sinusoidal (IEC 60068-2-6) | 5 g, 10 Hz to 500 Hz |
| Operating shock (IEC 60068-2-27) | 30 g, 11 ms half sine; 50 g, 3 ms half sine; 18 shocks at 6 orientations |

Environmental

Refer to the manual for the chassis you are using for more information about meeting these specifications.

| | |
|---|---------------------------------|
| Operating temperature (IEC 60068-2-1, IEC 60068-2-2) | -40 °C to 70 °C |
| Storage temperature (IEC 60068-2-1, IEC 60068-2-2) | -40 °C to 85 °C |
| Ingress protection | IP40 |
| Operating humidity (IEC 60068-2-78) | 10% RH to 90% RH, noncondensing |
| Storage humidity (IEC 60068-2-78) | 5% RH to 95% RH, noncondensing |
| Pollution Degree | 2 |
| Maximum altitude | 2,000 m |

Indoor use only.

Environmental Management

NI is committed to designing and manufacturing products in an environmentally responsible manner. NI recognizes that eliminating certain hazardous substances from our products is beneficial to the environment and to NI customers.

For additional environmental information, refer to the *Minimize Our Environmental Impact* web page at ni.com/environment. This page contains the environmental regulations and directives with which NI complies, as well as other environmental information not included in this document.

Waste Electrical and Electronic Equipment (WEEE)



EU Customers At the end of the product life cycle, all NI products must be disposed of according to local laws and regulations. For more information about how to recycle NI products in your region, visit ni.com/environment/weee.

电子信息产品污染控制管理办法（中国 RoHS）



中国客户 National Instruments 符合中国电子信息产品中限制使用某些有害物质指令 (RoHS)。关于 National Instruments 中国 RoHS 合规性信息, 请登录 ni.com/environment/rohs_china。(For information about China RoHS compliance, go to ni.com/environment/rohs_china.)

Refer to the *NI Trademarks and Logo Guidelines* at ni.com/trademarks for information on NI trademarks. Other product and company names mentioned herein are trademarks or trade names of their respective companies. For patents covering NI products/technology, refer to the appropriate location: **Help»Patents** in your software, the `patents.txt` file on your media, or the *National Instruments Patent Notice* at ni.com/patents. You can find information about end-user license agreements (EULAs) and third-party legal notices in the readme file for your NI product. Refer to the *Export Compliance Information* at ni.com/legal/export-compliance for the NI global trade compliance policy and how to obtain relevant HTS codes, ECCNs, and other import/export data. NI MAKES NO EXPRESS OR IMPLIED WARRANTIES AS TO THE ACCURACY OF THE INFORMATION CONTAINED HEREIN AND SHALL NOT BE LIABLE FOR ANY ERRORS. U.S. Government Customers: The data contained in this manual was developed at private expense and is subject to the applicable limited rights and restricted data rights as set forth in FAR 52.227-14, DFAR 252.227-7014, and DFAR 252.227-7015.

© 2011—2016 National Instruments. All rights reserved.

374644A-02 Feb16